

PHONE: (07) 5411 4209 (Option 2)
OR (02) 8004 3333 (Option 2)

WEBSITE: tbafirefly.com.au
EMAIL: sales@tbafirefly.com.au

MATERIAL DESCRIPTION

TBA Firefly™ retro-fit fire collars are made from steel and high pressure graphite intumescent.

CERTIFICATION

Warringtonfire Report No's:
FAS190234 RIR
FAS190235 RIR
FAS190236 RIR

Tested in Accordance with
AS1530.4-2014
Assessed in Accordance with
AS4072.1-2005

SIZES

Available in:
40mm, 50mm, 65mm, 80mm,
100mm, 150mm

APPLICATIONS

TBA Firefly™ FRF Fire Collars used to fire stop a variety of services which penetrate different Fire Resistant substrates.


For specific applications and FRLs achieved please refer to the referenced Compliance Reports. Must be installed in strict accordance with the construction details contained within the Compliance Reports.

TBA FIREFLY™


FRF FIRE COLLAR



FRF 150 Fire Collars



Nitrile Rubber Lagged Pair Coil
through 120 Min FRL Fire Rated
Plasterboard Wall



40-150mm OD uPVC Pipe through
120 Min FRL Fire Rated
Plasterboard Wall Intubatt Seal